

# LTZPFL200-00-6-W-24V

LED bar light, 6 LED rows, 200X26.3 illumination area, white, 24V



OPTO ENGINEERING

## 参数

### 光学规格

光源颜色, 峰值波长	white, 6300K
------------	--------------

### Lighting area

Length	(mm)	26,3
Width	(mm)	200

### 电气规格

照明延长线	Extension cable must be ordered separately <b>4</b>
-------	---

### Continuous mode

Supply voltage	(V)	24
Current	(mA)	360
Power consumption	W	8.7

### Pulsed mode

Supply voltage <b>1</b>	(V)	36
Max pulse current <b>2</b>	(mA)	1080

### 机械性能

长度	(mm)	212
宽度	(mm)	31,5
高度	(mm)	22

### 环境

防护等级	30
------	----

## 注释

1. 在恒定驱动电压下 (推荐36V, 最大48V)。占空比 = 0- 10%。最大脉冲宽度 = 10 ms。
2. 在恒定驱动电流下。占空比 = 0- 10%。最大脉冲宽度 = 10 ms。

## 订购信息

All accessories including lighting extension cables (CB series), diffusers (DFLT series), polarizers (PLLT series) and mounting brackets (CMLT series) must be ordered separately.

### 兼容产品



<b>TC23130</b>	适用于2/3"探测器的双远心镜头, 放大倍率0.068 x, C接口
<b>TC13144</b>	双远心镜头, 支持1/3"探测器, 放大倍率0.033 x, C接口
<b>TC12144</b>	适用于1/2"探测器的双远心镜头, 放大倍率0.044 x, C接口
<b>TC23144</b>	适用于2/3"探测器的双远心镜头, 放大倍率0.061 x, C接口



<b>TC2MHR120-C</b>	High resolution telecentric lens for 1" detectors, magnification 0.104x, C-mount
<b>TC2MHR120-F</b>	High resolution telecentric lens for 1" detectors, magnification 0.104x, F-mount
<b>TC2MHR120-E</b>	High resolution telecentric lens for 1" detectors, magnification 0.104x, mount M42X1 FD=16
<b>TC2MHR144-C</b>	High resolution telecentric lens for 1" detectors, magnification 0.089x, C-mount
<b>TC2MHR144-F</b>	High resolution telecentric lens for 1" detectors, magnification 0.089x, F-mount
<b>TC2MHR144-E</b>	High resolution telecentric lens for 1" detectors, magnification 0.089x, mount M42X1 FD=16
<b>TC4MHR120-C</b>	High resolution telecentric lens for 1.2" detectors, magnification 0.143x, C-mount
<b>TC4MHR120-F</b>	High resolution telecentric lens for 1.2" detectors, magnification 0.143x, F-mount



**TC4MHR120-E** High resolution telecentric lens for 1.2" detectors, magnification 0.143x, mount M42X1 FD=16

**TC4MHR144-C** High resolution telecentric lens for 1.2" detectors, magnification 0.122x, C-mount

**TC4MHR144-F** 适用于1.2"探测器的高分辨率远心镜头，放大倍率0.122x，F接口

**TC4MHR144-E** High resolution telecentric lens for 1.2" detectors, magnification 0.122x, mount M42X1 FD=16



**TC16M144** 适用于35 mm探测器的远心镜头，放大倍率0.245 x，F接口

**TC16M144-Q** 适用于35 mm探测器的远心镜头，放大倍率0.245 x，M58x0.75接口，FD = 6.56



**TC4K180-F** 适用于4k线扫描相机的远心镜头，放大倍率0.159x，F接口

**TC4K180-N** 适用于4k线扫描相机的远心镜头，放大倍率0.159x，M42X1接口，FD=10.56



**TC12K192** 适用于12k和16k线扫描相机的远心镜头，放大倍率0.320 x，M72 x 0.75接口



**TCDP2X144** 双放大倍率双远心镜头,最高支持2/3"探测器

**TCDP4X144** 双放大倍率双远心镜头,最高支持2/3"探测器



**MCZR018-004** 微距变焦旋转式装置, C接口



**LTDV1CH-17V** 1通道频闪控制器，可变电流5 mA - 17A



**CMLTZPFL** L-bracket, 40x30x12 mm



**DFLTZPFL200-00-6** Diffuser for LED bar light, 6 LED rows, 200X26.3 illumination area



**PLLTZPFL200-00-6-H** Horizontal polarizer for LED bar light, 6 LED rows, 200X26.3 illumination area

**PLLTZPFL200-00-6-V** Vertical polarizer for LED bar light, 6 LED rows, 200X26.3 illumination area